| | Page 1 of 2 | | | | |
|-------------------------------|---|---------------|--|--|--|
| | SPECIFICATION | | | | |
| | <u>024200 & 024300</u> | | | | |
| | Manufacturers standard remote controlled roller shall be supplied utilizing the following code/s. | | | | |
| | Manadatarore standard formate controlled folior shall be supplied dallizing the foliowing codore. | | | | |
| 024200 – | 4200 - Roller, Trenching, Sheepsfoot Drum, Remote Control, Articulated, 31 to 35 inch drum width, minimum operating weight 3,200 lbs., Vibratory, Diesel. Ref: Bomag 8500, Wacker RT 82-SC-3 | | | | |
| 024300 – | Roller, Trenching, Smooth Drum, Remote Control, Articulated, 31 to 35 inch drum width, minimum op 3,200 lbs., Vibratory, Diesel. Ref: Wacker RT 82-SC-3 | erating weigh | | | |
| | The following additional items shall be supplied | | | | |
| | | Accepted | | | |
| Mandatory : | o of the factory color shall be provided. Bidder must provide option pricing for having unit bid to be painted PENNDOT yellow. Reference 385, PPG 85246, Sherwin Williams 73266 or Napa 73266 shade only. | | | | |
| Comments | | | | | |
| • • | quipment shall comply with current EPA regulations for model year supplied. Non-compliant ll be rejected. | | | | |
| Comments | | | | | |
| acceptable) | lles and Platform (Area designed to be walked upon) shall be coated with anti-skid paint. (tape is not | | | | |
| Comments | | | | | |
| 4. Rollers sha | all be equipped with 2 scrapers per drum. | | | | |
| Comments | | | | | |
| 5. Rollers sha the roller. | all be equipped with a manufacturer's standard Infrared Remote Control with dual receiving eyes on | | | | |
| Comments | | | | | |
| 6. Diesel Eng | ine (Minimum 20 Horse Power) with electric start. | | | | |
| Comments | | | | | |
| 7. Drum width | n shall be 31 inch minimum to 35 inch maximum. | | | | |
| Comments | | | | | |
| 3. Roller shal | be equipped with a balanced center lift bracket. | | | | |
| Comments | | | | | |
| 9. Roller shal | l be equipped with an on board diagnostic system to diagnose fault codes. | | | | |
| Comments | | | | | |
| 10. Roller sha | all shut down automatically in the event of a roll over. | | | | |
| Comments | | | | | |
| 11. Both rolle | r drums shall be equipped with full hydraulic drives. | | | | |
| Comments | | | | | |
| 12. Roller sha | all have two speed settings in both forward and reverse. | | | | |
| Comments | | | | | |
| | nt panel shall have a lockable cover and all fill caps such as fuel, engine oil, hydraulic oil, radiator etc. Ible or located Inside a lockable housing or cabinet. All locks shall be keyed alike. | | | | |
| Comments | | | | | |
| | here shall be 5.0 hrs combined operator and mechanic training done at final county location per unit. | | | | |
| | | | | | |

| | | Page 2 of 2 | |
|--|--|--------------|--|
| 15. Warranty period shall be for 2 years, 100% parts & labor. Warranty and delivery per PCID 1075. The warranty start up date shall be defined as the date of transfer from the PennDOT Fleet Management Division to the designated county location. This will be considered the date of delivery to the county and NOT the date of delivery by the successful bidder to the department. The PennDOT Fleet Managment will supply the actual start-up date, equipment number, and serial number of the machine, via email, to the successful bidder. It is the responsibility of the successful bidder to ensure that the equipment manufacturer recognizes and applies the Department's actual warranty start-up date in their database. | | | |
| Comments | | | |
| 16. Paper work provided by manufacturer, vendor or carrier company at time of equipment delivery for signature will only be signed for verification of delivery. Signature will not endorse delivered equipment is free of defects or verification that equipment meets specification/quote. Acceptance of equipment is pending through inspection, with equipment meeting the specification/quote. Paper work will not be submitted for payment until all deficiencies are corrected, prior to purchase order delivery deadline. | | | |
| Comments | | | |
| 17. There shall be paper Operator, Parts and Maintenance & Repair manuals along with an electronic form of each manual on a USB thumb drive in Adobe PDF format. The paper operators manual shall have a weather resistant holder attached to the unit. | | | |
| Comments | | | |
| | | 9/7/2022 JAH | |