Dump Truck Specifications

Truck

GVW: 43,000

- Front Axle: 20k
- Rear Axle: 23k
- Drum Brakes
- Locking rear axle
- Spring Suspension
- Paccar PX-9 (Cummins L9) Engine 330 HP Diesel
- Jake Brake
- Single exhaust
- 10 spd. Manual transmission
- 315/80R22.5 steer tires
- 11R22.5 drive tires
- Polished Dura-Bright aluminum wheels
- Air ride driver seat, non-air ride passenger seat
- Toolbox under passenger seat
- Factory visor
- Color Black

Bed

- 10 1/2' Steel dump service
- Front Mount DA Hoist Std PTO/Pump
- ¼" HX450 (Hardox) steel floor
- 4" Channel on 12" centers
- 6" Channel longitudes on wood cushions
- 24" 3/16" steel sides w/ board gusset/Inside Radius
- Dirt shedding, tarp rod

36" Steel tailgate 3/16"
Pin type top hardware
Air bottom latches
37" High rear corners
36" Cab protector w/8" -10" lip – tarp ready
Two step ladder with Grab Handle
Splash shields, mud flaps
DOT/OEM Lighting
6 Light LED Strobe Package (4 in cab pro, one in each rear post)
¾" Hitch plate, D-Rings, bolt on pintle hitch, 7 pin round plug, glad hands
(factory air to be supplied to rear of truck)
Painted Black