

Resilient Flooring

RESILIENT FLOORING DESCRIPTION

- A. Characteristics: (Luxury Vinyl Tile / Enhanced Resilient Tile)
 - 1. Wear layer: 20 mil (0.5mm) or greater
 - 2. Finish: Enhanced wear layer
 - 3. Wear: Should meet ASTM Standards.
 - 4. Moisture: Approved up to 90% RH or above
 - 5. Complies with ASTM F 1700, Class III, Type A or B
 - 6. Must be FloorScore® certified
 - 7. Manufactured in a factory that has ISO 9001 and ISO 14001 certifications.

QUALITY ASSURANCE

- A. Have Manufacture flooring installed by a qualified installer of this type of flooring.
- B. In accordance with the technical instructions in the Installation Instructions, use all the accessories recommended by Manufacture when installing its flooring.
- C. Follow the instructions specified in the most recent version of Manufactures Installation Instructions.

DELIVERY, HANDLING, STORAGE

- A. Deliver the flooring to the installation site in Manufactures original packaging. Indicate the project name and handling instructions on the outside of the boxes.
- B. Advise the carrier of any damaged material and indicate it on the packing slip.
- C. Store the flooring inside, sheltered from extreme hot or cold temperatures. Place the material on a smooth level floor or where there is uniform solid support in a clean, dry well-ventilated area. Unstack the palettes. The long-term storage temperature must be maintained between 18°C (65°F) and 24°C (75°F). Protect adhesive and flooring material from freezing, extreme heat and direct sun exposure.
- D. Acclimatize the subfloor, all flooring material and adhesive for 48 hours before, during and after the installation by maintaining the room temperature between 18°C (65°F) and 24°C (75°F). The palettes should be unstacked 24 hours prior to use.
- E. Afterwards, maintain the room temperature between 18°C (65°F) and 29°C (85°F). Protect the material from direct sources of heat such as air vents and other types of heaters.
- F. Install the flooring after all other finishing work, including painting, have been completed.

2.01 RESILIENT FLOORING DESCRIPTION

- B. Characteristics: (Glue Down or Floating Floor)
 - 1. Type: Luxury Vinyl Tile / Enhanced Resilient Tile
 - 2. Installation: per manufactures recommendation for warranty compliance
 - 3. Wear Layer: 20 mil (0.5mm) or greater

Resilient Flooring

4. Finish: Enhanced Wear Layer
5. Size: To be determined by manufactures design options.
6. Complies with ASTM F 1700, Class III, Type A or B
7. Refer to the product's Technical Specifications data sheet for detailed specifications.
8. Choose from any of Manufactures complete line of colors (indicate the item number).
9. Must be FloorScore® certified
10. This product was manufactured in a factory that has ISO 9001 and ISO 14001 certifications.

2.02 ADHESIVE

Manufacture will only guarantee its flooring products with use of its recommended adhesives.

2.04 OTHER MATERIAL

- A. Subfloor repairs: use only Portland based patching compound or manufacturers recommended patching compound for substrate corrections.