

ATTACHMENT A

Signed Acknowledgement of DCNR DSA Specifications

1. The Contractor must choose the appropriate acknowledgement letter:
 - a. **DSA Contractor Acknowledgement of DSA Specifications (A.1)**
This form is used when the Contractor will be creating and supplying the DSA.
 - b. **DSA Quarry Letter of Intent (A.2)**
This form is used when the DSA will be created and supplied by a quarry *not owned* by the Contractor.
2. The appropriate form must be printed, completed in its entirety, signed, and dated.
 - a. Both A.1 and A.2 *must be signed only* by approved representatives of the Contractor and Quarry respectively.
 - b. The authorized representative must include their title with their signature.
 - c. Representatives must be knowledgeable of DSA and be prepared to answer all questions on the product.
3. The Contractor must then include the appropriate fully executed form with their bid response (either A.1 or A.2.).
DO NOT attach both acknowledgements.
4. Failure to comply with this requirement could result in a non-responsive determination and subsequent disqualification for the Contractor.



pennsylvania

DEPARTMENT OF CONSERVATION
AND NATURAL RESOURCES

BUREAU OF ADMINISTRATIVE SERVICES

CONTRACTOR ACKNOWLEDGEMENT OF DSA PRODUCT

(FORM MUST BE COMPLETED BY BIDDING CONTRACTOR)

Solicitation # 6100060932

FD07 - Bald Eagle

Spruce Run

Approximate Tonnage – 5,000

(Tonnage is estimated and can increase or decrease based on the needs of the Department.)

By signing this acknowledgement I, _____ (Print Name), an authorized representative of _____ (Name of Contractor), confirms that _____ (Name of Contractor) has the ability to competently create and supply certified Driving Surface Aggregate (DSA) for the Solicitation listed above that meets the following specifications.

Passive Sieve	Low Percentage	High Percentage
1 ½ inch	100%	--
¾ inch	65%	97%
#4	30%	65%
#16	15%	30%
#200*	11%	15%

The fines passing the #200 sieve must be rock material. No clay or silt soil may be added. Limestone material passing the #200 sieve may be used to make up a deficit in the distribution of sandstone aggregate rock, and vice versa. All added material passing the #200 sieve must be derived from rock material that conforms to program specifications. The amount of particles passing the #200 sieve will be determined using the washing procedures specified in PTM No. 100.

*If the Plasticity Index for the Material is 2 or below, then the #200 sieve is permitted to be 11-17%.

pH: 6 – 12.45 as measured by EPA 9045C

LA Abrasion: < 45% loss based on Los Angeles Abrasion test, AASHTO T-96 [ASTM C 131]

Plasticity Index: ≤ 4 based on ASTM D4318 – Standard Test Method for Liquid Limit, Plastic Limit, and Plasticity Index of Soils.

Optimum Moisture: Material will be delivered and placed at optimum moisture content, or up to 2% below that value, as determined for that particular source. The optimum percentage moisture will be determined using Proctor Test ASTM D698, procedure C, Standard.

Signature of Authorized Representative

Date

Division of Procurement & Supply

Rachel Carson State Office Building | P.O. Box 8769 | Harrisburg, PA 17105-8769 | 717.783.3332 | F 717.787.8624 | www.dcnr.pa.gov



pennsylvania

DEPARTMENT OF CONSERVATION
AND NATURAL RESOURCES

BUREAU OF ADMINISTRATIVE SERVICES

QUARRY ACKNOWLEDGEMENT OF DSA PRODUCT - LETTER OF INTENT

(FORM MUST BE COMPLETED BY SUPPLYING QUARRY)

Solicitation # 6100060932

FD07 - Bald Eagle

Spruce Run

Approximate Tonnage – 5,000

(Tonnage is estimated and can increase or decrease based on the needs of the Department.)

By signing this Letter of Intent I, _____ (Print Name), an authorized representative of _____ (Name of Company), confirms that _____ (Location or Name of Quarry) has the ability to competently create and supply to _____ (Name of Contractor) certified Driving Surface Aggregate (DSA) for the Solicitation listed above that meets the following specifications.

Passive Sieve	Low Percentage	High Percentage
1 ½ inch	100%	--
¾ inch	65%	97%
#4	30%	65%
#16	15%	30%
#200*	11%	15%

The fines passing the #200 sieve must be rock material. No clay or silt soil may be added. Limestone material passing the #200 sieve may be used to make up a deficit in the distribution of sandstone aggregate rock, and vice versa. All added material passing the #200 sieve must be derived from rock material that conforms to program specifications. The amount of particles passing the #200 sieve will be determined using the washing procedures specified in PTM No. 100.

*If the Plasticity Index for the Material is 2 or below, then the #200 sieve is permitted to be 11-17%.

pH: 6 – 12.45 as measured by EPA 9045C

LA Abrasion: < 45% loss based on Los Angeles Abrasion test, AASHTO T-96 [ASTM C 131]

Plasticity Index: ≤ 4 based on ASTM D4318 – Standard Test Method for Liquid Limit, Plastic Limit, and Plasticity Index of Soils.

Optimum Moisture: Material will be delivered and placed at optimum moisture content, or up to 2% below that value, as determined for that particular source. The optimum percentage moisture will be determined using Proctor Test ASTM D698, procedure C, Standard.

Signature of Authorized Representative

Date

Division of Procurement & Supply

Rachel Carson State Office Building | P.O. Box 8769 | Harrisburg, PA 17105-8769 | 717.783.3332 | F 717.787.8624 | www.dcnr.pa.gov