



**JWC Environmental**  
 2850 S. Red Hill Ave. Suite 125  
 Santa Ana, CA 92705  
 Phone: 949.833.3888  
 Toll Free: 800.331.2277  
 Fax: 714.242.0240  
**Page: 1**

**Quote # 34845A**

Please address Purchase Orders to:  
**JWC Environmental**  
**2850 S. Red Hill Ave. Suite 125**  
**Santa Ana, CA 92705**  
**USA**  
**Fax: 714.242.0240**

**To** SCI-Greene  
 169 Progress Drive  
 Waynesburg, PA 15370  
 US

**Rep** DAS Group  
**Phone** 724-327-8979

We thank you for your inquiry and are pleased to quote pricing and delivery on the equipment listed below. This quotation is subject to terms and conditions listed on the JWC Environmental "Terms and Conditions" page, and any comments and exception listed below.

All orders will be billed the applicable sales tax, based on the "ship to address", unless a valid tax exemption certificate is provided prior to shipment.

<b>Project</b>	SCI Greene	<b>Bid Date</b>	
<b>Quote Date</b>	09/21/2016	<b>FOB</b>	Origin
<b>Submittals</b>	6 weeks after receipt of order	<b>Expire Date</b>	11/13/2016
<b>Ship Equipment</b>	12 weeks after approval/release	<b>Terms</b>	NET 30 DAYS
<b>Consulting Engineer</b>			
<b>Spec. Section</b>			

**LINE ITEMS**

Line No	Qty	Part/Description
1	1	<p><b>AGE3200-480</b>            One (1) Model AGE3200-480-2.5 Auger Monster system suitable for up to 1500 GPM in 24"w x 50"d channel and solids discharge nominally 49" above the top of channel (refer to JWC Environmental Auger Monster Evaluation for additional performance data).            Scope of supply to include:            * Grinder with 32" cutter stack using 7-tooth cam cutters in hardened alloy steel, tungsten carbide mechanical seals with BUNA-N elastomers rated for 60 psi, green epoxy-coated gray iron end housings &amp; high-flow side rails, 43:1 speed reducer and 10 hp XPFC explosion-proof 230-460v/3ph/60Hz electric motor            * AMA3200-480 auger, 35 deg. inclination, 304 stainless steel trough &amp; casings, 1/4" perforated screen, nom. 20" dia. alloy-steel spiral with nylon brush, 12" dia. alloy-steel transport spiral with tapered element, 2250 mm transport segment, bottom discharge, 160:1 speed reducer, 2 hp XPFC explosion-proof 230-460v/3ph/60Hz electric motor coated with green epoxy paint, and stainless steel spray wash with manual ball &amp; bronze explosion-proof solenoid valves            * Pivot frame and support components fabricated in 304 stainless steel</p> <p>One (1) PC2251D motor controller in a NEMA 4X 304 SST enclosure accepting 230v/3ph/60Hz or 460v/3ph/60Hz input power, includes IEC starters with over-current protection, jam-sensing current transformers, micro-PLC, operator interface and analog ultrasonic transducers</p> <p>Four (4) Operation and Maintenance manuals</p>

**Price \$102,625.00**

**Clarification**

- Standard one year warranty is included.
- One (1) day of start-up supervision by JWCE is included.