

**Specifications – Invitation for Bid 6100063667**

**ISSUING OFFICE**



**COMMONWEALTH OF PENNSYLVANIA  
DEPARTMENT OF GENERAL SERVICES  
BUREAU OF PROCUREMENT  
1800 Herr Street, 2<sup>nd</sup> Floor  
Harrisburg, PA 17103**

**ON BEHALF OF**

**PENNSYLVANIA DEPARTMENT OF HUMAN SERVICES  
(DHS)**

**05/21/2025**

## 1. **PURPOSE:**

This Invitation for Bid 6100063667 will be for the purchase of **one (1) new and unused Chassis Cab with 16' Dry Freight Van Body and Liftgate** for the Pennsylvania Department of Human Services.

## 2. **METHOD OF AWARD:**

It is the intent of the Commonwealth to make a single award of item(s) listed in the IFB to the lowest responsive and responsible bidder. The Commonwealth Reserves the right to award by line item if it determines that it is in the best interest of the Commonwealth to do so.

## 3. **ISSUING OFFICE:**

**Dan Covell** | Commodity Specialist  
Equipment Procurement Section  
Department of General Services | Bureau of Procurement  
1800 Herr Street, 2<sup>nd</sup> Floor | Harrisburg, PA 17103  
Phone: 717-346-3828 Fax 717-346-3820  
[dcovell@pa.gov](mailto:dcovell@pa.gov)

## 4. **SPECIFICATIONS:**

PSP is looking to purchase **one (1) new and unused Gas Powered Chassis Cab with 16' Dry Freight Van Body and Liftgate**

- ***New and Unused Current Model Year***
- ***2-Door Regular Cab Configuration***
- ***Wheelbase/Cab-to-Axle to accommodate 16' Dry Freight Box Body and liftgate***
- ***Two Wheel Drive (4x2, RWD)***
- ***Dual Rear Wheel (DRW)***
- ***Minimum 19,000-lb GVW***
- Paint:
  - White
- Powertrain:
  - Minimum 6.4L displacement gasoline engine
  - Minimum 6-Speed Automatic Transmission
  - Minimum 380-amp alternator
  - Minimum Limited Slip Rear Differential

- Wheels & Tires
  - 19.5" x 6.0" Gray Painted Steel Disc Wheels
  - Two (2) Front All-Position Tires
  - Four (4) Rear All-Terrain/Traction Tires
- Exterior
  - Two (2) Front Tow Hooks
  - Steel Front Bumper
  - Alligator Style Hood (not tilt forward)
  - Front Fender Flares
  - Variable Intermittent Wiper
  - Cab Clearance Lights
  - Power Adjustable, Heated Trailer Tow Mirrors
  - Factory/OEM Rearview Camera (including installation at rear of body in location for optimum use)
  - Factory/OEM Step for entry/egress from the cab
- Interior
  - Cloth 40/20/40 Split Bench Front Seat w/Driver Lumbar
  - Upfitter Switches
  - AM/FM Stereo w/wireless device connectivity (Bluetooth)
  - Six (6) Speakers
  - Power Door Locks w/Remote Keyless Entry
  - Power Windows
  - Tilt Steering Column
  - Speed/Cruise Control
  - Full Vinyl/Rubber Floor Covering
- Miscellaneous:
  - Must Provide total of four (4) keys/fobs
  - 5-lb ABC Fire Extinguisher mounted behind seat
  - Triangle Kit mounted behind seat
  - First Aid Kit shipped loose
- 16' Dry Freight Van Body
  - 79.12" Inside Height" Inside Height, 197.13" Inside Length, 92.13" Inside Width
  - Subframe - 3" I-beam crossmembers on 12" centers with 6" channel longrail
  - Mylar tape applied between all steel subframe components and extruded aluminum lower bottom rails to prevent corrosion.
  - Aluminum extruded anti-skid inverted T overlay including extruded scuff and glassboard subpan.

- Two (2) Drain with kazoo at for extruded floor at rear endplate and front
- Threshold – Steel galvanized angle flush to rear
- Rear door - Overhead roll-up door with spacer kit for installation, vinyl seal kit and monobolted
- Rear frame – Galvannealed steel - painted Imron White. Includes Built-in header design and clearance light protector and rain deflector
- 12” aluminum curbside and roadside grab-handles
- Roof - .032” One-piece aluminum sheet with anti-snag roof bows on 24” centers with crowned roof design to prevent water/ice pooling
- Side and front wall - Extruded aluminum top and bottom rails with **6mm DuraPlate White Panels**
- Two (2) Rows E Track **surface mounted** to side wall at 26.5” and 55.5” from floor to center
- Mount OEM Camera in a location to provide safe unobstructed view when vehicle is in reverse
- Liftgate
  - **2,500-lb Capacity**
  - Galvanized steel finish
  - Grease points at all critical rotation points
  - 48” x 80” wedge-type aluminum platform
  - Dual cart stops
  - Bolt-on steps
  - Hand held control
  - Cab Cut-off switch
  - **Gravity down**