

clamped every 18" min.

Connection shall be made using the factory OEM trailer wiring harness.

All connections shall be water tight.

Brake lights shall function with turn signals.

Wire shall be 7 way (1-10 guage; 6-12 guage) per ATA color code,

<u>N</u>O

TOD CJW

7 WAY CONNECTOR

WIRING DIAGRAM/

ВЧ

REVISIONS

ယ


DATE 11-29-06 08-12-08 11-12-09

DATE 07-22-95

WHM SHEET 1 OF 1

EQN-80A

connector.



EQUIPMENT DIVISION SPECIFICATION UNIT FOR APPROVAL MANUFACTURER SHALL BE SUBMITTED, IN WRITING, TO THE ANY ALTERNATE OR ADDITIONAL DESIGNS RECOMMENDED BY THE

NOTE: THERE SHALL BE A COLE HERSEE, HOLDER 11750 MOUNTED IN THE TONGUE AREA.

PA DEPARTMENT OF TRANSPORTATION

POSSIBLE

CHKD BY WHM SHEET 1 OF 1	CHKIDBY WHM		ACT	08-21-14 ACT ACT 10-09-97	3
EQN-84	SCALE N/A	DLW	JFM	07-11-13 JFM DRAWN BY	2
IONO	OFECIFICATIONS	OF	Ş H	05-16-07 KNH	_
TIONIO LIND			ВΥ	DATE	<u>N</u> 0
	TRAILED EBONT END	TDA	0,	REVISIONS	

SAFETY ADMINISTRATION (NHTSA) IN THAT: THIS VEHICLE SHALL COMPLY WITH THE RULES OF THE NATIONAL HIGHWAY TRAFFIC

ROAD SURFACE, AND THE UPPER EDGE NOT MORE THAN 60in. ABOVE IT. NUMBER 108. THE CENTER OF THE MATERIAL MUST NOT BE LESS THAN 15in. ABOVE THE HEIGHT AS OTHER RETROFLECTIVE DEVICES CURRENTLY REQUIRED BY STANDARD THE MOUNTING HEIGHT OF THE HORIZONTAL STRIPES ARE RESTRICTED TO THE SAME

REFLECTIVE MATERIAL SHALL BE APPLIED TO THE HORIZONTAL BAR OF THE REAR UNDERRIDE DEVICE IN ADDITION TO THE FLOOR LEVEL HORIZONTAL STRIPE. THE UPPER 12in. BY TWO INCHES WIDE, INDICATING THE WIDTH AND HEIGHT OF THE TRAILER CORNERS ARE TO BE MARKED BY TWO 90 DEGREE ANGLE BRACKETS OF WHITE STRIPES

THE COLORS SHALL BE PLACED IN ALTERNATING SEQUENCE WITH MORE THAN UNIFORM AS PRACTICAL AND INDICATE THE FULL LENGTH AND WIDTH OF THE VEHICLE. CLOSEING DISTANCE TO IT. THE DISTRIBUTION OF SPACES AND MATERIALS SHALL BE AS THE CONFIGURATION SHALL IDENTIFY THE VEHICLE AS TO ITS ESTIMATED SIZE AND THE TWO-THIRDS OF THE MATERIAL IN COLOR.

OR 3M SCOTCHLITE CONSPICUITY SHEETING BACKING REFLEXITE CONSPICUITY II SYSTEM SERIES 980 MATERIAL SHALL BE RED/SILVER CONTINUOUS CONSPICUITY TAPE SHALL BE REFLECTORIZED. 2in. WIDE, MATERIAL SHALL BE APPLIED. DA DEDADTMENT OF TDANSDORTATION

THE MOST CURRENT REGULATIONS SHALL BE ADHERED TO.

T'A	DETAK	_ 		ANSPO	TA DETAK I MEN I OF I KANSTOK I A HON
_	REVISIONS		CON	CONSPICUITY TAPE	Y TAPE
NO.	NO. DATE BY	ВҮ	STRIPI	NG REQ	STRIPING REQIREMENTS
1	05-16-02 DWG	DWG			
2	11-03-06	Mro	2 11-03-06 CJW DLW SCALE N/A	SCALE N/A	EQN-127A
3	01-02-09	HHM	11-07-97	VMQ AB G, MIC	3 01-02-09 MHH ^{DATE} 11-07-97 OHKOBY DMA SHEET 1 OF 1

