

Department of Agriculture Stake Truck Specifications

Model: New Ford 4X4 Truck Super Duty F-550 Reg Cab/Dual Rear Wheel Stake Body Truck
In addition to the XL Package Standard Features, vehicle should include the following:

DIMENSIONS

GVWR: 19,500 lbs. Payload Plus Upgrade Package

Wheelbase: 169"

Cab to axle: 84"

POWERTRAIN

7.3L V-8 DEVCT variable valve control 335HP V-8 Engine

10-speed automatic

Part-time Four-wheel drive

Electronic transfer case shift with auto locking hub control

Mechanical limited slip differential

Dual 68 AH/65 AGM Batteries

410 Amp Dual Alternators

SUSPENSION AND HANDLING

Snow Plow Prep Package

Front and Rear Heavy-Duty shock absorbers

Rigid axle rear suspension with rear anti-roll bar

Hydraulic power-assist re-circulating ball steering

4-wheel anti-lock ventilated disc brakes

225/70R19.5 All Terrain front and rear tires

19.5 x 6-inch front and dual rear argent steel wheels

BODY EXTERIOR

Department of Agriculture Stake Truck Specifications

Running boards

Black fender flares

Black front bumper with 2 front tow hooks

Black grille

Manually extendable power trailer tow mirrors with convex spotter

Exterior backup alarm

CONVENIENCE

Power door locks with 2 stage unlocking and keyfob activated door locks

Cruise control with steering wheel mounted controls and tilt and telescopic steering column

Power windows

Illuminated glove box

Upfitter switches

CAB INTERIOR

Manual air conditioning

Cabin air filter

Cloth full headliner

Full vinyl floorcovering

40-20-40 Vinyl Split Bench Seat with Medium Dark Slate Trim

8 inch primary touchscreen display with AM/FM stereo, seek-scan, 4 speakers

Gauges: Tachometer, Oil pressure gauge, Engine temperature gauge, transmission temperature gauge, Engine hour meter

6 Airbags: Driver/Passenger frontal impact, seat mounted side impact, Safety Canopy System

Safety Kit: First aid kit, Fire Extinguisher, Triangle Reflector Kit

Department of Agriculture Stake Truck Specifications

Electric brake controller

STAKE BODY

144 x 96-inch light weight, high strength aluminum construction platform

Aluminum substructure with 3" channel crossmembers on 12" centers, 5" mounting "J" sills full length

Heavy-duty aluminum extruded rub rail

.140 all-aluminum diamond plate design floor

42-inch aluminum bulkhead with punched out window grill

Removable manual interlocking 42-inch high sides with 3 extruded aluminum upright posts per side section with 6" extruded aluminum horizontal slates (6 inch opening between slats)

Aluminum splash guards

Recessed fuel cap

Thick rubber mudflaps with stainless weights

20,000-lb Class 5 hitch with ICC bumper and 7-RV Trailer Wiring Plug per SAE guidance and safety chain eyes with combo pintle hook and ball

All body lighting shall be LED