

Boat Specs

- 2025 23' All Welded Aluminum Outboard Boat with 8' Walk Around Cabin
- Aft bulkhead with locking swing door
- SeaStar hydraulic steering, standard helm, stainless steering wheel w/knob
- 8-position Blue Sea waterproof switch panel #BSS4378, 2 ea 12v power points, trumpet horn, LED navigation lights, anchor light (both USCG Approved), 2 ea pantograph wipers, LED red/white chart light mounted under electronics box
- 1 ea LED Deck Light
- Remote Spot Light ACR RCL-95
- 2 ea standard helm seats on sliders & seat shock absorber
- 2 ea aft seat/storage boxes w/cushions
- Bow Deck w/ locking top hatch
- Anchor Locker Set-up includes BRM-2 roller, 16lb claw anchor, 20ft of 1/4" HT chain, 150ft of 1/2" 3-strand rope, ss swivel and tie off inside locker
- Radar Arch
- Webasto AT-2000 Kerosene Heater with 6-gallon tank, defroster on dash, thermostat, fuel gauge mounted on portside dash and CO monitor
- Locking Gunwale Storage Boxes (4 doors)
- 2 ea side dive doors (port & starboard) drop in style
- Trim Tabs, Lenco electric with LED indicator switch
- Ladder - Armstrong 3-step with face plate mount on corner of swim step
- Garmin GPSMAP 8612xsv w/ built-in sounders, GMR Fantom 18x Radome, down/side vu scan transom mount transducer (GT51M-TM), external GPS 24xd antenna, NMEA 2000
- VHF with Shakespeare 8ft antenna, HD ss ratchet mount
- Ritchie Compass
- FLIR M364 with JCU-1 controller installed/calibrated
- Twin Yamaha 115's Mechanical 4-stroke, turnkey includes dual top mount controls, CL5 Display, key switch panel w/lanyard, power trim and tilt, Pro-X Control cables, Racor fuel filter/water separators, aluminum props and rigging/installation

- 3ea AGM batteries in boxes (2 starting, 1 house), BS 8689 battery management panel, 2ea ACR's, battery cables, engine battery cable extensions, power posts, fuse block & fuses
- EZ Loader Tandem Axle Galvanized Bunk Trailer - 7500# capacity includes disc brakes on both axles, channel glide bunk system, oil bath hubs, side load guides, LED Lights, spare tire & carrier, tie downs, fit to boat
- ¼" 5086 alloy one-piece bottom plate
- 3/16" side & deck plates
- 114 gallon fuel tank w/EPA compliant Evap standards using certified components
- Reinforced chine extrusion (proprietary) with double welds on the inside
- Welded in sealed self bailing aluminum deck with non-skid flooring
- 7" gunwale boxes with storage (optional locking doors available)
- Foam flotation below deck
- Hull cut-outs port and starboard
- Zinc & mount, transducer bracket(s), tow eye (double)
- Large oval 2-3/4" gunwale extrusion (proprietary)
- Full width swim step/bracket
- ½" transom plate w/5" channel stiffening
- Wide engine clamping area for twin engine applications
- Bilge pump w/auto float switch
- 8" cleats (4)
- SeaStar Hydraulic steering system with ss steering wheel
- LED Navigation lights, all around light - USCG Approved
- 8-position Switch panel
- Horn
- Power point